

Dual N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Advanced trench cell design
- ☒ Extremely low threshold voltage
- ☒ ESD 2KV



1.2 Applications

- ☒ Portable appliances
- ☒ Battery management

1.3 Quick reference

- ☒ $BV \geq 16\text{ V}$
- ☒ $P_{tot} \leq 1.56\text{ W}$
- ☒ $I_D \leq 10\text{ A}$
- ☒ $R_{DS(ON)} \leq 13\text{ m}\Omega @ V_{GS} = 4.5\text{ V}$
- ☒ $R_{DS(ON)} \leq 15\text{ m}\Omega @ V_{GS} = 2.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Source(S1)	 Top View SOT 23-6L	
2	Drain(D1)		
3	Source(S2)		
4	Gate(G2)		
5	Drain(D2)		
6	Gate(G1)		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_A = 25\text{ }^{\circ}\text{C}$	16	-	V
V_{GS}	Gate-Source Voltage	$T_A = 25\text{ }^{\circ}\text{C}$	-	± 12	V
I_D^*	Drain Current	$T_A = 25\text{ }^{\circ}\text{C}$, $V_{GS} = 4.5\text{ V}$	-	10	A
$I_{DM}^{*,**,***}$	Pulsed Drain Current	$T_A = 25\text{ }^{\circ}\text{C}$, $V_{GS} = 4.5\text{ V}$	-	24	A
P_{tot}^*	Total Power Dissipation	$T_A = 25\text{ }^{\circ}\text{C}$	-	1.56	W
		$T_A = 100\text{ }^{\circ}\text{C}$	-	0.62	
T_{stg}	Storage Temperature		- 55	150	$^{\circ}\text{C}$
T_J	Junction Temperature		-	150	$^{\circ}\text{C}$
I_S^*	Diode Forward Current	$T_A = 25\text{ }^{\circ}\text{C}$	-	10	A
$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient		-	80	$^{\circ}\text{C} / \text{W}$

Notes :

- * Surface Mounted on 1 in² pad area, $t \leq 10\text{ sec}$
- ** Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ8817A	

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ8817A	SOT23-6			3000	

Note: KUAJIEXIN defines “ Green ” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)

6. Electrical Characteristics (T_A = 25 °C Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _{DS} = 250 μA	16	–	–	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = 250 μA	0.5	–	1.0	V
I _{DSS}	Drain Leakage Current	V _{DS} = 12 V, V _{GS} = 0 V	–	–	1	μA
		T _J = 85 °C	–	–	30	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 10 V, V _{DS} = 0 V	–	–	± 100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} = 4.5 V, I _{DS} = 8 A	–	10	13	m Ω
		V _{GS} = 2.5 V, I _{DS} = 5 A	–	14	15	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} = 8 A, V _{GS} = 0 V	–	–	1.2	V
Dynamic Characteristics ^b						
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = 10 V Frequency = 10 KHz	–	963	–	pF
C _{oss}	Output Capacitance		–	301	–	
C _{rss}	Reverse Transfer Capacitance		–	284	–	
t _{d(on)}	Turn-on Delay Time	V _{DS} = 7.5 V, V _{GEN} = 4.5 V, R _G = 4.5 Ω, R _L = 0.93 Ω, I _{DS} = 8 A	–	0.1	–	μS
t _r	Turn-on Rise Time		–	0.03	–	
t _{d(off)}	Turn-off Delay Time		–	0.03	–	
t _f	Turn-off Fall Time		–	5.3	–	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{DS} = 7.5 V, V _{GS} = 10 V, I _{DS} = 8 A	–	22.6	–	nC
Q _{gs}	Gate-Source Charge		–	2.7	–	
Q _{gd}	Gate-Drain Charge		–	3.9	–	


Notes :

a : Pulse test ; pulse width ≤ 300 μs, duty cycle ≤ 2 %


b : Guaranteed by design, not subject to production testing

7. Typical Characteristics


Power Capability




Current Capability







Safe Operation Area







Transient Thermal Impedance



7. Typical Characteristics (cont.)


Output Characteristics

On Resistance

Transfer Characteristics

Normalized Threshold Voltage


7. Typical Characteristics (cont.)



8. Package Dimensions

SOT23-6L



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	0.09	1.45
A1	0.00	0.15
A2	0.90	1.30
D	2.90 BSC	
E	2.80 BSC	
E1	1.50	1.75
c	0.09	0.20
b	0.35	0.50
e	0.95 BSC	
e1	1.90 BSC	
L	0.10	0.60