

P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- Advanced trench cell design
- Low Thermal Resistance



1.2 Applications

- Motor drivers
- DC - DC Converter

1.3 Quick reference

- $BV \geq -40\text{ V}$
- $R_{DS(ON)} \leq 38\text{ m}\Omega @ V_{GS} = -10\text{ V}$
- $P_{tot} \leq 25\text{ W}$
- $R_{DS(ON)} \leq 55\text{ m}\Omega @ V_{GS} = -4.5\text{ V}$
- $I_D \leq -10\text{ A}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Gate(G)		
2	Drain(D)		
3	Source(S)		

Top View
SOT-89



3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V _{DS}	Drain-Source Voltage	T _C = 25 °C	-40	-	V
V _{GS}	Gate-Source Voltage	T _C = 25 °C	-	± 20	V
I _D	Drain Current	T _C = 25 °C, V _{GS} = -10 V	-	-10	A
I _{DM} ^{*,**}	Pulsed Source Current	T _C = 25 °C, V _{GS} = -10 V	-	-25	A
P _{tot} [*]	Total Power Dissipation	T _C = 25 °C	-	35	W
T _{stg}	Storage Temperature		- 55	150	°C
T _J	Junction Temperature		-	150	°C
I _S	Diode Forward Current	T _C = 25 °C	-	-10	A
R _{θJC} [*]	Thermal Resistance- Junction to Ambient		-	3.5	°C / W

Notes :

- * Surface Mounted on 1 in² pad area, t ≤ 10 sec
- ** Pulse width ≤ 10 μs, duty cycle ≤ 1 %
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ10P04S	<div style="display: inline-block; border: 1px solid black; padding: 2px;"> 10P04 YWWXXX </div> YWW: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ10P04S	SOT89			1000	

Note: KUAJIEXIN defines " Green " as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)



快捷冠

KJ10P04S

6. Electrical Characteristics (T_C = 25 °C Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _D = -250 μA	-40	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = -250 μA	-1.5	-	-2.5	V
I _{DSS}	Zero Gate Voltage Source Current	V _{DS} = -32 V, V _{GS} = 0 V	-	-	-1	μA
		T _J = 85 °C	-	-	-30	μA
I _{GSS}	Gate Leakage Current	V _{GS} = ± 20 V, V _{DS} = 0 V	-	-	± 100	nA
R _{DS(ON)} ^a	Drain-Source On-State Resistance	V _{GS} = -10 V, I _D = -10 A	-	33	38	mΩ
		V _{GS} = -4.5 V, I _D = -5 A	-	46	55	mΩ
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} = -10 A, V _{GS} = 0 V	-	-	-1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} = -10 A, dI _{SD} /dt = 100 A/μs	-	13.5	-	ns
Q _{rr}	Reverse Recovery Charge		-	2.8	-	nC
Dynamic Characteristics^b						
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = -20 V Frequency = 1 MHz	-	1169	-	pF
C _{oss}	Output Capacitance		-	79	-	
C _{rss}	Reverse Transfer Capacitance		-	64	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} = -20 V, V _{GEN} = -10 V, R _G = 4.5 Ω, R _L = 2 Ω, I _D = -10 A	-	13	-	ns
t _r	Turn-on Rise Time		-	43	-	
t _{d(off)}	Turn-off Delay Time		-	135	-	
t _f	Turn-off Fall Time		-	84	-	
Gate Charge Characteristics^b						
Q _g	Total Gate Charge	V _{GS} = -10 V, V _{DS} = -20 V, I _{DS} = -10 A	-	20	-	nC
Q _{gs}	Gate-Source Charge		-	5.5	-	
Q _{gd}	Gate-Drain Charge		-	2.5	-	


Notes :

- a : Pulse test ; pulse width ≤ 300 μs, duty cycle ≤ 2 %
- b : Guaranteed by design, not subject to production testing




7. Typical Characteristics

Power Capability




T_j - Junction Temperature (°C)

Current Capability




T_j - Junction Temperature (°C)

Safe Operation Area



-V_{DS} - Drain-Source Voltage (V)


Thermal Transient Impedance




Square Wave Pulse Duration (sec)

7. Typical Characteristics (cont.)


Output Characteristics




Drain-Source On Resistance



Transfer Characteristics




Gate Threshold Voltage






7. Typical Characteristics (cont.)


Drain-Source On Resistance




Body Diode Characteristics



Capacitance




Gate Charge





8.Package Dimensions

SOT89-3L



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047