

P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Advanced trench cell design



1.2 Applications

- ☒ LCD TV appliances
☒ LCDM appliances
- ☒ High power inverter system

1.3 Quick reference

- ☒ $BV \geq -60\text{ V}$
☒ $P_{\text{tot}} \leq 2\text{ W}$
☒ $I_D \leq -20\text{ A}$
- ☒ $R_{\text{DS(ON)}} \leq 23\text{ m}\Omega @ V_{\text{GS}} = -10\text{ V}$
☒ $R_{\text{DS(ON)}} \leq 28\text{ m}\Omega @ V_{\text{GS}} = -4.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1,2,3	Source(S)	 Top View SOP8	
4	Gate(G)		
5,6,7,8	Drain(D)		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-60	-	V
V_{GS}	Gate-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-	± 20	V
I_D	Drain Current (DC)	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	-20	A
		$T_C = 100\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	-18	A
$I_{DM}^{*,***}$	Drain Current (Pulsed)	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	-30	A
P_{tot}	Drain power dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	-	2	W
T_{stg}	Storage Temperature		-55	150	$^{\circ}\text{C}$
T_J	Junction Temperature		-	150	$^{\circ}\text{C}$
I_S	Continuous-Source Current	$T_C = 25\text{ }^{\circ}\text{C}$	-	-20	A
$R_{\theta JA}^{**}$	Thermal Resistance- Junction to Ambient		-	62.5	$^{\circ}\text{C/W}$
$R_{\theta JC}^{**}$	Thermal Resistance- Junction to Case		-	3.5	

Notes :

* Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$

** Mounted on Large Heat Sink

*** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ20P06S	20P06 YWWXXX YWWXXX: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ20P06S	SOP8			3000	

Note: KUAJIEXIN defines “ Green ” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC / JEDEC J-STD-020C)

6. Electrical Characteristics ($T_A=25\text{ }^{\circ}\text{C}$ Unless Otherwise Noted)

Symbol	Parameter	Conditions	Min.	Typ.	Max.	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} = 0 V, I _{DS} = - 250 μA	- 60	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} = V _{GS} , I _{DS} = - 250 μA	- 1	-	- 3	V
I _{DSS}	Drain Leakage Current	V _{DS} = - 48 V , V _{GS} = 0 V	-	-	- 1	μA
I _{GSS}	Gate Leakage Current	V _{GS} = 0 V, V _{GS} = ± 20 V	-	-	±100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} = - 10 V, I _{DS} = - 15 A	-	20	23	mΩ
		V _{GS} = - 4.5 V, I _{DS} = - 10 A	-	25	28	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} = - 15 A, V _{GS} = 0 V	-	-	- 1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} = - 15 A, dI _{SD} / dt = 100 A / μs	-	23	-	nS
Q _{rr}	Reverse Recovery Charge		-	23	-	nC
Dynamic Characteristics ^b						
C _{iss}	Input Capacitance	V _{GS} = 0 V, V _{DS} = - 30 V Frequency = 1 MHz	-	4584	-	pF
C _{oss}	Output Capacitance		-	178	-	
C _{rss}	Reverse Transfer Capacitance		-	133	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} = - 30 V, V _{GEN} = - 10 V, R _G = 3.9 Ω, R _L = 2 Ω, I _{DS} = - 15 A	-	66	-	nS
t _r	Turn-on Rise Time		-	101	-	
t _{d(off)}	Turn-off Delay Time		-	465	-	
t _f	Turn-off Fall Time		-	205	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{DS} = - 30 V, V _{GS} = - 10 V, I _{DS} = - 15 A	-	72	-	nC
Q _{gs}	Gate-Source Charge		-	19	-	
Q _{gd}	Gate-Drain Charge		-	9.8	-	


Notes :

a : Pulse test ; pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$


b : Guaranteed by design, not subject to production testing

7. Typical Characteristics (Cont.)


Power Capability




Current Capability



Safe Operation Area




Transient Thermal Impedance




7. Typical Characteristics (Cont.)


Output Characteristics




Drain-Source On Resistance







Transfer Characteristics



Normalized Threshold Voltage






7. Typical Characteristics (Cont.)



8. Package Dimensions

SOP8



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	1.35	1.75
A1	0.00	0.25
A2	1.15	1.50
D	4.80	5.00
E	5.80	6.20
E1	3.80	4.00
c	0.19	0.27
b	0.33	0.53
e	1.27 BSC	
L	0.40	1.27

Notes :

1. Jedec outline : MS-012AA
2. Dimensions " D " does not include mold flash, protrusions and gate burrs shall not exceed .15 mm (.006 in) per side .
3. Dimensions " E1 " does not include inter-lead flash, or protrusions. Inter-lead flash and protrusions shall not exceed .25 mm (.010 in) per side.