

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Low Thermal Resistance



1.2 Applications

- ☒ MB and NB
- ☒ Motor drivers
- ☒ Half-bridge Drivers

1.3 Quick reference

- ☒ $BV \geq 100\text{ V}$
- ☒ $R_{DS(ON)} \leq 17\text{ m}\Omega @ V_{GS} = 10\text{ V}$
- ☒ $P_{tot} \leq 35\text{ W}$
- ☒ $R_{DS(ON)} \leq 24\text{ m}\Omega @ V_{GS} = 4.5\text{ V}$
- ☒ $I_D \leq 31\text{ A}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1,2,3	Source(S)	 Top View PDFN3.3x3.3-8L	
5,6,7,8	Drain(D)		
4	Gate(G)		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	100	-	V
V_{GS}	Gate-Source Voltage	$T_C = 25\text{ }^{\circ}\text{C}$	-	± 20	V
I_D^*	Drain Current	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	31	A
$I_{DM}^{*,**,***}$	Pulsed Source Current	$T_C = 25\text{ }^{\circ}\text{C}, V_{GS} = 10\text{ V}$	-	112	A
P_{tot}^*	Total Power Dissipation	$T_C = 25\text{ }^{\circ}\text{C}$	-	35	W
T_{stg}	Storage Temperature		- 55	150	$^{\circ}\text{C}$
T_J	Junction Temperature		-	150	$^{\circ}\text{C}$
$R_{\theta JA}^*$	Thermal Resistance- Junction to Ambient		-	62.5	$^{\circ}\text{C/W}$
$R_{\theta JC}^*$	Thermal Resistance- Junction to Case		-	6	

Notes:

- * Surface Mounted on 1 in² pad area, $t \leq 10\text{ sec}$
- ** Pulse width $\leq 10\text{ }\mu\text{s}$, duty cycle $\leq 1\%$
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ30N10QGS	30N10S YWWXXX YWWXXX: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ30N10QGS	PDFN3.3x3.3-8L	-	-	5000	

Note: KUAIJIEXIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C)

6. Electrical Characteristics (T_A=25°C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	100	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	1.0	1.8	2.6	V
I _{DSS}	Drain Leakage Current	V _{DS} =100 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±20 V, V _{DS} =0 V	-	-	±100	nA
R _{DS(ON)}	On-State Resistance	V _{GS} =10 V, I _{DS} =20 A	-	15	17	mΩ
		V _{GS} =4.5 V, I _{DS} =10 A	-	21	24	mΩ
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} =20 A, V _{GS} =0 V	-	-	1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} =20 A, V _{GS} =0 V dI _{SD} /dt=100 A/μs	-	24	-	ns
Q _{rr}	Reverse Recovery Charge		-	125	-	nC
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{GS} =0 V, V _{DS} =50 V Frequency=1 MHz	-	1230	-	pF
C _{oss}	Output Capacitance		-	256	-	
C _{rss}	Reverse Transfer Capacitance		-	2.8	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =50 V, V _{GS} =10 V, R _G =4.5 Ω, R _L =12.5 Ω, I _{DS} =20 A	-	8.4	-	ns
t _r	Turn-on Rise Time		-	6.3	-	
t _{d(off)}	Turn-off Delay Time		-	24	-	
t _f	Turn-off Fall Time		-	6	-	
Switching Parameters						
Q _g	Total Gate Charge	V _{DS} =50 V, V _{GS} =10 V, I _{DS} =20 A	-	26	-	nC
Q _{gs}	Gate-Source Charge		-	6.1	-	
Q _{gd}	Gate-Drain Charge		-	4.8	-	

Notes:

- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%
- Guaranteed by design, not subject to production testing


7. Typical Characteristics

Power Capability




T_{mp} – Mounting Point Temp. (°C)

Current Capability




T_{mp} – Mounting Point Temp. (°C)

Safe Operation Area




Transient Thermal Impedance




7. Typical Characteristics (Cont.)


Output Characteristics




On Resistance



Transfer Characteristics




Normalized Threshold Voltage




7. Typical Characteristics (Cont.)


Normalized On Resistance




Diode Forward Current



Capacitance



Gate Charge



8. Package Dimensions

PDFN3.3x3.3-8L Package

