

P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Low Thermal Resistance



1.2 Applications

- ☒ LCD TV appliances
- ☒ High power inverter system
- ☒ LCDM appliances

1.3 Quick reference

- ☒ $BV \geq -40\text{ V}$
- ☒ $R_{DS(ON)} \leq 2.8\text{ m}\Omega @ V_{GS} = -10\text{ V}$
- ☒ $P_{tot} \leq 300\text{ W}$
- ☒ $R_{DS(ON)} \leq 4.5\text{ m}\Omega @ V_{GS} = -4.5\text{ V}$
- ☒ $I_D \leq -180\text{ A}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1,2,3	Source	 Top View LFPAK 5x6	
4	Gate		
Tab	Drain		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C=25^{\circ}\text{C}$	-	-40	V
V_{GS}	Gate-Source Voltage	$T_C=25^{\circ}\text{C}$	-	± 20	V
$I_{D^{***}}$	Drain Current	$T_C=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-180	A
		$T_C=100^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-166	A
I_{DM}^{***}	Pulsed Source Current	$T_C=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-700	A
P_{tot}^{*}	Drain Power Dissipation	$T_C=25^{\circ}\text{C}$	-	300	W
T_{stg}	Storage Temperature		-55	175	$^{\circ}\text{C}$
T_J	Junction Temperature		-	175	$^{\circ}\text{C}$
I_S	Continuous-Source Current	$T_C=25^{\circ}\text{C}$	-	-180	A
I_{AS}	Single Pulsed Avalanche Current	$V_{DD}=-40\text{ V}, L=0.1\text{ mH}$	-	-110	A
E_{AS}	Single Pulsed Avalanche Energy	$V_{DD}=-40\text{ V}, L=1.0\text{ mH}$	-	1250	mJ
$R_{\theta JA}^{**}$	Thermal Resistance-Junction to Ambient		-	42	$^{\circ}\text{C/W}$
$R_{\theta JC}^{**}$	Thermal Resistance-Junction to Case		-	0.4	

Notes:

- * Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$
- ** Surface Mounted on 1 in² pad area, $t \leq 10\text{ sec}$
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ025P04LF	025P04 YWW01 AAAAAA YWW01: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ025P04LF	LFPK5x6	-	-	5000	

6. Electrical Characteristics (T_A=25°C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	-40	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	-1.0	-	-2.5	V
I _{DSS}	Drain Leakage Current	V _{DS} =-32 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{GS} =±20 V, V _{DS} =0 V	-	-	±100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} =-10 V, I _{DS} =-50 A	-	2.5	2.8	mΩ
		V _{GS} =-4.5 V, I _{DS} =-30 A	-	3.9	4.5	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} =-50 A, V _{GS} =0 V	-	-	-1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} =-50 A, V _{GS} =0 V, dI _{SD} /dt=100 A/μs	-	28	-	ns
Q _{rr}	Reverse Recovery Charge		-	26	-	nC
Dynamic Characteristics ^b						
C _{iSS}	Input Capacitance	V _{GS} =0 V, V _{DS} =-20 V Frequency=1 MHz	-	16177	-	pF
C _{oSS}	Output Capacitance		-	1067	-	
C _{rSS}	Reverse Transfer Capacitance		-	301	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =-20 V, V _{GEN} =-10 V, R _G =3.9 Ω, R _L =0.4 Ω, I _{DS} =-50 A	-	18	-	ns
t _r	Turn-on Rise Time		-	124	-	
t _{d(off)}	Turn-off Delay Time		-	337	-	
t _f	Turn-off Fall Time		-	140	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{DS} =-20 V, V _{GS} =-10 V, I _{DS} =-20 A	-	276	-	nC
Q _{gs}	Gate-Source Charge		-	65	-	
Q _{gd}	Gate-Drain Charge		-	35	-	

Notes:


- a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%
- b. Guaranteed by design, not subject to production testing

7. Typical Characteristics


Power Capability




Current Capability



Safe Operating Area




Transient Thermal Impedance




7. Typical Characteristics (Cont.)


Output Characteristics




On Resistance







Transfer Characteristics



Normalized Threshold Voltage




7. Typical Characteristics (Cont.)



8. Package Dimensions

LFPK5x6 Package



Symbol	Dimensions In Millimeters	
	MIN.	MAX.
A	1.00	1.30
A1	0	0.15
A2	0.98	1.12
b	0.35	0.50
b1	0.32	0.46
b2	4.02	4.41
b3	4.00	4.37
c	0.19	0.25
c1	0.17	0.23
c2	0.24	0.30
c3	0.22	0.28
D	4.45	4.70
D1	-	4.45
E	4.95	5.30
E1	3.50	3.70
e	1.27 BSC.	

Symbol	Dimensions In Millimeters	
	MIN.	MAX.
H	5.95	6.25
i	-	0.25
L	0.40	0.85
L1	0.27	0.57
L2	0.80	1.30
θ	0°	8°