

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Low gate charge



1.2 Applications

- ☒ Motor driver appliances
- ☒ High power inverter system
- ☒ Adapter appliances

1.3 Quick reference

- ☒ $BV \geq 150\text{ V}$
- ☒ $P_{\text{tot}} \leq 52\text{ W}$
- ☒ $I_D \leq 22\text{ A}$
- ☒ $R_{\text{DS(ON)}} \leq 45\text{ m}\Omega @ V_{\text{GS}} = 10\text{ V}$
- ☒ $R_{\text{DS(ON)}} \leq 48\text{ m}\Omega @ V_{\text{GS}} = 4.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Gate(G)	 Top View TO-252	
2	Drain(D)		
3	Source(S)		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V _{DS}	Drain-Source Voltage	T _C =25°C	-	150	V
V _{GS}	Gate-Source Voltage	T _C =25°C	-	±20	V
I _D *	Drain Current	T _C =25°C, V _{GS} =10 V	-	22	A
		T _C =100°C, V _{GS} =10 V	-	14	A
I _{DM} *	Drain Current (Pulsed)	T _C =25°C, V _{GS} =10 V	-	50	A
P _{tot}	Drain power dissipation	T _C =25°C	-	52	W
T _{stg}	Storage Temperature		-55	150	°C
T _J	Junction Temperature		-	150	°C
I _S	Continuous-Source Current	T _C =25°C	-	30	A
E _{AS}	Single Pulsed Avalanche Energy	V _{DD} =50 V, L=1.0 mH	-	78	mJ
R _{θJA} **	Thermal Resistance-Junction to Ambient		-	50	°C/W
R _{θJC} **	Thermal Resistance-Junction to Case		-	2.4	

Notes:

- * Pulse width ≤ 300 μs, duty cycle ≤ 2%
- ** Surface Mounted on 1 in² pad area, t ≤ 10 sec
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ20N15KL	20N15L YWWXXX YWWXXX: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ20N15KL	TO-252	-	-	2500	

6. Electrical Characteristics (T_A=25°C Unless Otherwise Noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	150	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	0.4	-	1.2	V
I _{DSS}	Drain Leakage Current	V _{DS} =120 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{DS} =0 V, V _{GS} =±20 V	-	-	±100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} =10 V, I _{DS} =10 A	-	40	45	mΩ
		V _{GS} =4.5 V, I _{DS} =5 A	-	41	48	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} =10 A, V _{GS} =0 V	-	-	1.3	V
t _{rr}	Reverse Recovery Time	I _{DS} =10 A, V _{GS} =0 V dI _{SD} /dt=100 A/μs	-	50	-	ns
Q _{rr}	Reverse Recovery Charge		-	107	-	μC
Dynamic Characteristics ^b						
C _{iss}	Input Capacitance	V _{GS} =0 V, V _{DS} =75 V Frequency=1 MHz	-	1304	-	pF
C _{oss}	Output Capacitance		-	79	-	
C _{rss}	Reverse Transfer Capacitance		-	12	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =75 V, V _{GEN} =10 V, R _G =3.9 Ω, R _L =7.5 Ω, I _{DS} =10 A	-	6	-	ns
t _r	Turn-on Rise Time		-	11	-	
t _{d(off)}	Turn-off Delay Time		-	36	-	
t _f	Turn-off Fall Time		-	67	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{DS} =75 V, V _{GS} =10 V, I _{DS} =10 A	-	34	-	nC
Q _{gs}	Gate-Source Charge		-	4	-	
Q _{gd}	Gate-Drain Charge		-	5	-	

Notes:


- Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%
- Guaranteed by design, not subject to production testing

7. Typical Characteristics


Power Capability




Current Capability



Safe Operating Area




Transient Thermal Impedance




7. Typical Characteristics (Cont.)


Output Characteristics




On Resistance







Transfer Characteristics



Normalized Threshold Voltage




7. Typical Characteristics (Cont.)



8. Package Dimensions

TO-252 Package



Symbol	Dimensions in Millimeters	
	MIN.	MAX.
A	2.19	2.38
A1	0.02	0.13
D	5.30	6.40
E	6.35	6.80
E1	5.20	5.50
c	0.40	0.60
c1	0.40	0.60
b	0.55	0.85
e	2.30 BCS	
L	1.00	1.80
L1	0.70	1.80
L2	0.70 BCS	
L3	2.40	2.80
H	9.20	10.40