

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Low gate charge



1.2 Applications

- ☒ Motor driver appliances
- ☒ High power inverter system
- ☒ Adapter appliances

1.3 Quick reference

- ☒ $BV \geq 40\text{ V}$
- ☒ $P_D \leq 35\text{ W}$
- ☒ $I_D \leq 80\text{ A}$
- ☒ $R_{DS(ON)} \leq 3.0\text{ m}\Omega @V_{GS} = 10\text{ V}$
- ☒ $R_{DS(ON)} \leq 4.5\text{ m}\Omega @V_{GS} = 4.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
4	Gate(G)		
5, 6, 7, 8	Drain(D)		
1, 2, 3	Source(S)		

Bottom View
DFN 3.3x3.3-8L

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C=25^{\circ}\text{C}$	-	40	V
V_{GS}	Gate-Source Voltage	$T_C=25^{\circ}\text{C}$	-	± 20	V
$I_D^{*,***}$	Drain Current (DC)	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	80	A
		$T_C=100^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	61	A
I_{DM}^{*}	Pulsed Source Current	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	240	A
P_D	Total Power Dissipation	$T_C=25^{\circ}\text{C}$	-	35	W
E_{AS}^{*}	Single Pulsed Avalanche Energy	$V_{DD}=40\text{ V}, L=1.0\text{ mH}$	-	138	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	150	$^{\circ}\text{C}$
$R_{\theta JA}^{**}$	Thermal Resistance-Junction to Ambient		-	62.5	$^{\circ}\text{C/W}$
$R_{\theta JC}^{**}$	Thermal Resistance-Junction to Case		-	3.5	

Notes:

- * Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$
- ** Surface Mounted on 1 in^2 pad area, $t \leq 10\text{ sec}$
- *** Limited by bonding wire

4. Marking Information

Product Name	Marking
KJ2R8N04Q	2R8N04 YWWXXX YWW: Date Code

5. Ordering Code

Product Name	Package	Reel Size	Tape width	Quantity	Note
KJ2R8N04Q	DFN 3.3x3.3-8L	13"	12 mm	5000	

Note: KUAJIE XIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C)

6. Electrical Characteristics (T_A=25°C unless otherwise noted)





Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	40	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	1	-	3	V
I _{DSS}	Zero Gate Voltage Source Current	V _{DS} =32 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{DS} =0 V, V _{GS} =±20 V	-	-	±100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} =10 V, I _{DS} =30 A	-	2.8	3.0	mΩ
		V _{GS} =4.5 V, I _{DS} =20 A	-	3.9	4.5	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} =30 A, V _{GS} =0 V	-	-	1.3	V
t _{rr}	Reverse Recovery Time	I _{DS} =30 A, V _{GS} =0V dI _{SD} /dt=100 A/μs	-	47	-	ns
Q _{rr}	Reverse Recovery Charge		-	35	-	nC
Dynamic Characteristics ^b						
C _{iSS}	Input Capacitance	V _{GS} =0 V, V _{DS} =20 V Frequency=1 MHz	-	2683	-	pF
C _{oSS}	Output Capacitance		-	1027	-	
C _{rSS}	Reverse Transfer Capacitance		-	76	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =20 V, V _{GEN} =10 V, R _G =3.9 Ω, R _L =1 Ω, I _{DS} =30 A	-	10	-	ns
t _r	Turn-on Rise Time		-	68	-	
t _{d(off)}	Turn-off Delay Time		-	49	-	
t _f	Turn-off Fall Time		-	40	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{DS} =20 V, V _{GS} =10 V, I _{DS} =30 A	-	51	-	nC
Q _{gs}	Gate-Source Charge		-	11	-	
Q _{gd}	Gate-Drain Charge		-	9	-	

Notes:

a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.


b. Guaranteed by design, not subject to production testing.

7. Typical Characteristics




7. Typical Characteristics (cont.)


Output Characteristics




On Resistance







Transfer Characteristics



Normalized Threshold Voltage




7. Typical Characteristics (cont.)



8. Package Dimensions

DFN 3.3x3.3-8L Package



Symbol	Dimensions in Millimeters	
	MIN	MAX
A	0.70	0.80
A1	0	0.05
A3	0.20 REF	
b	3.25	3.35
D	3.25	3.35
D2	2.30	2.40
E	1.85	1.95
E2	0.25	0.35
e	0.35	0.55
L	0.62 BSC	