

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Advanced trench cell design
- ☒ Low Thermal Resistance



1.2 Applications

- ☒ Motor drivers
- ☒ DC-DC Converter

1.3 Quick reference

- ☒ $BV \geq -30\text{ V}$
- ☒ $P_D \leq 50\text{ W}$
- ☒ $I_D \leq -80\text{ A}$
- ☒ $R_{DS(ON)} \leq 7.5\text{ m}\Omega @V_{GS} = -10\text{ V}$
- ☒ $R_{DS(ON)} \leq 12\text{ m}\Omega @V_{GS} = -4.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1,2,3	Source	 Top View PDFN5x6-8L	
4	Gate		
5,6,7,8	Drain		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_A=25^{\circ}\text{C}$	-30	-	V
V_{GS}	Gate-Source Voltage	$T_A=25^{\circ}\text{C}$	-	± 20	V
$I_D^{*, **}$	Drain Current (DC)	$T_A=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-80	A
		$T_A=100^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-63	A
$I_{DM}^{*, **, ***}$	Drain Current (Pulsed)	$T_A=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-360	A
P_D^*	Drain power dissipation	$T_A=25^{\circ}\text{C}$	-	50	W
I_S	Continuous-Source Current	$T_A=25^{\circ}\text{C}$	-	-80	A
E_{AS}^*	Single Pulsed Avalanche Energy	$V_{DD}=-15\text{ V}, L=0.5\text{ mH}$	-	269	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	150	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance, Junction to Ambient		-	62.5	$^{\circ}\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction to Case		-	2.5	

Notes:

- * Surface mounted on 1 in² pad area, $t \leq 10\text{ sec}$.
- ** Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.
- *** Limited by bonding wire.

4. Marking Information

Product Name	Marking
KJ80P03G	80P03 XXXXXX

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ80P03G	PDFN 5x6-8L	13"	12 mm	5000

Note: KUAJIEXIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C).

6. Electrical Characteristics (T_A=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =-250 μA	-30	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250 μA	-1.0	-1.5	-2.0	V
I _{DSS}	Drain Leakage Current	V _{DS} =-30 V, V _{GS} =0 V	-	-	-1	μA
I _{GSS}	Gate Leakage Current	V _{GS} =±20 V, V _{DS} =0 V	-	-	±100	nA
R _{DS(ON)} ^a	On-State Resistance	V _{GS} =-10 V, I _D =-30 A	-	5.8	7.5	mΩ
		V _{GS} =-4.5 V, I _D =-20 A	-	9	12	
Diode Characteristics						
V _{SD} ^a	Diode Forward Voltage	I _{SD} =-1A, V _{GS} =0 V	-	-	-1.2	V
Dynamic Characteristics ^b						
C _{iss}	Input Capacitance	V _{GS} =0 V, V _{DS} =-15 V, Frequency=1 MHz	-	4320	-	pF
C _{oss}	Output Capacitance		-	534	-	
C _{rss}	Reverse Transfer Capacitance		-	493	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =-15 V, I _{DS} =-15 A V _{GEN} =-10 V, R _G =2.5 Ω,	-	19	-	ns
t _r	Turn-on Rise Time		-	15	-	
t _{d(off)}	Turn-off Delay Time		-	65	-	
t _f	Turn-off Fall Time		-	36	-	
Gate Charge Characteristics ^b						
Q _g	Total Gate Charge	V _{GS} =-10 V, V _{DS} =-15 V, I _{DS} =-15 A	-	45	-	nC
Q _{gs}	Gate-Source Charge		-	8	-	
Q _{gd}	Gate-Drain Charge		-	12	-	

Notes :

a : Pulse test ; pulse width ≤ 300 μs, duty cycle ≤ 2%

b : Guaranteed by design, not subject to production testing

7. Typical Characteristics

Figure 1. Output Characteristics




Figure 2. Transfer Characteristics




Figure 3. On-Resistance vs. Drain Current




Figure 4. Capacitance




Figure 5. Gate Charge





Figure 6. Body Diode Forward Voltage



7. Typical Characteristics (cont.)

Figure 7. On-Resistance vs. Junction Temperature




Figure 8. Threshold Voltage vs. Junction Temperature




Figure 9. Transient Thermal Impedance






Figure 10. Safe operation area



8. Package Dimensions

PDFN 5x6-8L Package



Symbol	Dimensions in Millimeters	
	MIN	MAX
A	0.80	1.00
A1	0.00	0.05
b	0.35	0.49
c	0.254 REF	
D	4.90	5.10
E	5.70	5.90
E1	3.40 REF	
e	1.27 BSC	
F	1.40 REF	
G	0.60 REF	
H	5.95	6.20
J	0.95 BSC	
K	4.00 REF	
L1	0.10	0.18
L	-	0.15
P	1.00 REF	
R	0.25 REF	
θ	6°	14°