

P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Surface-mounted package
- ☒ Low gate charge
- ☒ Ultra-low on-resistance



1.2 Applications

- ☒ PWM applications
- ☒ Load switch

1.3 Quick reference

- ☒ $BV \geq -30\text{ V}$
- ☒ $P_{tot} \leq 25\text{ W}$
- ☒ $I_D \leq -15\text{ A}$
- ☒ $R_{DS(ON)} \leq 16\text{ m}\Omega @V_{GS} = -10\text{ V}$
- ☒ $R_{DS(ON)} \leq 30\text{ m}\Omega @V_{GS} = -4.5\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1,2,3	Source	 Top View PDFN3.3x3.3-8L	
4	Gate		
5,6,7,8	Drain		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_A=25^{\circ}\text{C}$	-30	-	V
V_{GS}	Gate-Source Voltage	$T_A=25^{\circ}\text{C}$	-	± 20	V
I_D	Drain Current	$T_A=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-15	A
		$T_A=70^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-11	A
I_{DM}^*	Pulsed Source Current	$T_A=25^{\circ}\text{C}, V_{GS}=-10\text{ V}$	-	-60	A
P_{tot}	Total Power Dissipation	$T_A=25^{\circ}\text{C}$	-	25	W
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	150	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient		-	62.5	$^{\circ}\text{C}/\text{W}$
$R_{\theta JC}$	Thermal Resistance-Junction to Case		-	5	

Notes:

* Surface mounted on 1 in² pad area, $t \leq 10\text{ sec}$.

** Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.

*** Limited by bonding wire.

4. Marking Information

Product Name	Marking
KJ15P03Q	15P03 XXXX

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ15P03Q	PDFN 3.3x3.3-8L	13"	12 mm	5000


Note: KUAJIEYIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C).

6. Electrical Characteristics (T_A=25°C unless otherwise noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =-250 μA	-30	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250 μA	-1	-1.5	-2.5	V
I _{DSS}	Drain Leakage Current	V _{DS} =-30 V, V _{GS} =0 V	-	-	-1	μA
I _{GSS}	Gate Leakage Current	V _{GS} =±20 V, V _{DS} =0 V	-	-	±100	nA
R _{DS(ON)}	On-State Resistance	V _{GS} =-10 V, I _D =-15 A	-	14	16	mΩ
		V _{GS} =-4.5 V, I _D =-10 A	-	20	30	
g _{fs}	Forward transconductance	V _{GS} =-5 V, I _D =-15 A	-	19	-	S
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =-15 V, V _{GS} =-0 V, f=1 MHz	-	1040	-	pF
C _{oss}	Output Capacitance		-	180	-	
C _{rss}	Reverse Transfer Capacitance		-	125	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =-15 V, V _{GEN} =-10 V, R _{GEN} =1 Ω, I _D =-15 A	-	10	-	ns
t _r	Turn-on Rise Time		-	5.5	-	
t _{d(off)}	Turn-off Delay Time		-	26	-	
t _f	Turn-off Fall Time		-	9	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge	V _{DS} =-15 V, V _{GS} =-10 V, I _D =-10 A	-	19	-	nC
Q _{gs}	Gate-Source Charge		-	9.6	-	
Q _{gd}	Gate-Drain Charge		-	3.6	-	
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _{SD} =-5 A, V _{GS} =0 V	-	0.8	-1.2	V

7. Typical Characteristics


Power Capability




Current Capability



Safe Operation Area




Thermal Transient Impedance




7. Typical Characteristics (cont.)


Output Characteristics




Drain-Source On Resistance



Transfer Characteristics




Gate Threshold Voltage




7. Typical Characteristics (cont.)


Drain-Source On Resistance




Body Diode Characteristics



Capacitance




Gate Charge



8. Package Dimensions

PDFN 3.3x3.3-8L Package



Symbol	Dimensions in Millimeters	
	MIN	MAX
A	0.65	0.85
A1	/	0.05
b	0.20	0.40
c	0.10	0.25
D	3.15	3.45
D1	2.90	3.10
D2	2.30	2.60
E	3.15	3.45
E1	2.90	3.20
E2	1.54	1.94
E3	0.18	0.48
e	0.55	0.75
L	0.30	0.50
L1	0.06	0.20
H	0.31	0.52
t	0.00	0.13
θ	/	12°