

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☑ Surface-mounted package
- ☑ T_J 175°C
- ☑ Advanced trench cell design
- ☑ MSL1



1.2 Applications

- ☑ BMS appliances
- ☑ Drones
- ☑ High power inverter system
- ☑ Light electric vehicles

1.3 Quick reference

- ☑ $BV \geq 100\text{ V}$
- ☑ $P_D \leq 319\text{ W}$
- ☑ $I_D \leq 260\text{ A}$
- ☑ $R_{DS(ON)} \leq 2.3\text{ m}\Omega @V_{GS} = 10\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Gate	 Top View TOLL-8L	
2,3,4,5,6,7,8	Source		
9	Drain		


3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C=25^{\circ}\text{C}$	100	-	V
V_{GS}	Gate-Source Voltage	$T_C=25^{\circ}\text{C}$	-	± 20	V
I_D	Drain Current (DC)	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	260	A
		$T_C=100^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	184	A
I_{DM}^*	Drain Current (Pulsed)	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	1040	A
P_D	Drain Power Dissipation	$T_C=25^{\circ}\text{C}$	-	319	W
I_S	Continuous-Source Current	$T_C=25^{\circ}\text{C}$	-	260	A
E_{AS}	Single Pulsed Avalanche Energy	$V_{DD}=40\text{ V}, L=0.5\text{ mH}$	-	1020	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	175	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient		-	40	$^{\circ}\text{C/W}$
$R_{\theta JC}$	Thermal Resistance-Junction to Case		-	0.47	$^{\circ}\text{C/W}$

Notes:

- * Pulse width $\leq 300\text{ }\mu\text{s}$, duty cycle $\leq 2\%$.
- ** Surface mounted on minimum footprint pad area.
- *** Limited by bonding wire.

4. Marking Information

Product Name	Marking
KJ023N10T	

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ023N10T	TOLL-8L	13"	24 mm	2000

Note: KUAJIEXIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C)

6. Electrical Characteristics (T_A=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	100	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	2	-	4	V
I _{DSS}	Zero Gate Voltage Source Current	V _{DS} =80 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{DS} =0 V, V _{GS} =±20 V	-	-	±100	nA
R _{DS(ON)}	On-State Resistance	V _{GS} =10 V, I _{DS} =75 A	-	2.0	2.3	mΩ
Diode Characteristics						
V _{SD}	Diode Forward Voltage	V _{GS} =0 V, I _{SD} =75 A	-	0.88	1.3	V
t _{rr}	Reverse Recovery Time	V _{GS} =0 V, I _{SD} =75 A, dI _{SD} /dt=100 A/μs	-	80	-	ns
Q _{rr}	Reverse Recovery Charge		-	195	-	nC
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =50 V, V _{GS} =0 V, Frequency=1 MHz	-	8530	-	pF
C _{oss}	Output Capacitance		-	1130	-	
C _{rss}	Reverse Transfer Capacitance		-	110	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =50 V, V _{GEN} =10 V, R _G =6 Ω, R _L =2.5 Ω, I _{DS} =75 A	-	65	-	ns
t _r	Turn-on Rise Time		-	78	-	
t _{d(off)}	Turn-off Delay Time		-	87	-	
t _f	Turn-off Fall Time		-	35	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge	V _{DS} =50 V, V _{GS} =10 V, I _{DS} =75 A	-	140	-	nC
Q _{gs}	Gate-Source Charge		-	43	-	
Q _{gd}	Gate-Drain Charge		-	40	-	

7. Typical Characteristics




Figure 1. Power Capability




Figure 2. Current Capability




Figure 3. Safe Operation Area




Figure 4. Transient Thermal Impedance




Figure 5. Output Characteristics




Figure 6. On Resistance

7. Typical Characteristics (cont.)




Figure 7. Transfer Characteristics




Figure 8. Normalized Threshold Voltage




Figure 9. Normalized On Resistance




Figure 10. Diode Forward Current




Figure 11. Capacitance





Figure 12. Gate Charge

8. Package Dimensions

TOLL-8L Package



Symbol	Dimensions in Millimeters		
	MIN	NOM	MAX
A	2.20	2.30	2.40
b	0.60	0.70	0.90
b1	0.30		0.50
c	0.40	0.50	0.60
D	10.28	10.38	10.48
D1	3.20	3.30	3.40
D2	6.85	6.95	7.05
D3		4.18 REF	
E	9.80	9.90	10.0
E1	9.70	9.80	9.90

Symbol	Dimensions in Millimeters		
	MIN	NOM	MAX
E2	8.00	8.10	8.20
e		1.20 BSC	
H	11.48	11.68	11.88
L	1.60	1.80	2.10
L1	1.00	1.15	1.30
L2		0.60 TYPE	
L3		0.60 TYPE	
K		2.90 TYPE	
θ	8°	10°	12°

9. Revision History and Disclaimer

Revision History

Revision	Date	Major changes
0.1	2022-01-21	Release of formal version.
0.2	2022-03-18	Update package POD.
0.3	2022-06-28	Update package POD.
0.4	2023-10-25	Update parameters, including I_D , P_D , typical characteristics etc.
0.5	2025-09-22	Update package POD, notes, marking information. Add revision history.

Disclaimer

KJX-SEMI reserves the right to improve product design, function and reliability without notice.