

P-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☒ Advanced trench cell design
- ☒ Low Thermal Resistance



1.2 Applications

- ☒ Motor drivers
- ☒ DC\DC Converter

1.3 Quick reference

- ☒ $BV \geq -150\text{ V}$
- ☒ $P_D \leq 156\text{ W}$
- ☒ $I_D \leq -33\text{ A}$
- ☒ $R_{DS(ON)} \leq 90\text{ m}\Omega @V_{GS} = -10\text{ V}$
- ☒ $R_{DS(ON)} \leq 100\text{ m}\Omega @V_{GS} = -6\text{ V}$

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1	Gate(G)	 Top View TO-252	
2	Drain(D)		
3	Source(S)		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V _{DS}	Drain-Source Voltage	T _C =25°C	-150	-	V
V _{GS}	Gate-Source Voltage	T _C =25°C	-	±20	V
I _D	Drain Current (DC)	T _C =25°C, V _{GS} =-10 V	-	-33	A
I _D	Drain Current (DC)	T _C =100°C, V _{GS} =-10 V	-	-21	A
I _{DM} *	Pulsed Source Current	T _C =25°C, V _{GS} =-10 V	-	-132	A
P _D	Power Dissipation	T _C =25°C	-	156	W
E _{AS}	Single Pulsed Avalanche Energy	V _{DD} =-50 V, L=1 mH	-	32	mJ
T _{stg} , T _J	Operating Junction and Storage Temperature Range		-55	150	°C
R _{θJA}	Thermal Resistance, Junction to Ambient		-	62.5	°C/W
R _{θJC}	Thermal Resistance, Junction to Case		-	0.8	

Notes:

- * Pulse width ≤ 300 μs, duty cycle ≤ 2%.
- ** Surface mounted on 1 in² pad area, t ≤ 10 sec.
- *** Limited by bonding wire.

4. Marking Information

Product Name	Marking
KJ38P15K	KJ38P15K XXXXXX

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ38P15K	TO-252	13"	16 mm	2500

Note: KUAJIEXIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C)

6. Electrical Characteristics (T_C=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _D =-250 μA	-150	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =-250 μA	-1.0	-	-2.5	V
I _{DSS}	Zero Gate Voltage Source Current	V _{DS} =-150 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{DS} =0 V, V _{GS} =±20 V	-	-	±100	nA
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =-10 V, I _D =-15 A	-	80	90	mΩ
		V _{GS} =-6 V, I _D =-10 A	-	85	100	mΩ
Diode Characteristics						
V _{SD}	Diode Forward Voltage	I _{SD} =-15A, V _{GS} =0 V	-	-	-1.3	V
t _{rr}	Reverse Recovery Time	I _{SD} =-15 A dI _{SD} /dt=100 A/μs	-	74	-	ns
Q _{rr}	Reverse Recovery Charge		-	153	-	nC
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{GS} =0 V, V _{DS} =-75 V Frequency=1 MHz	-	6600	-	pF
C _{oss}	Output Capacitance		-	130	-	
C _{rss}	Reverse Transfer Capacitance		-	111	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =-75 V, V _{GEN} =-10 V R _G =3.3 Ω, I _D =-15 A	-	12	-	ns
t _r	Turn-on Rise Time		-	26	-	
t _{d(off)}	Turn-off Delay Time		-	28	-	
t _f	Turn-off Fall Time		-	35	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge	V _{DS} =-75 V, V _{GS} =-10 V I _{DS} =-15 A	-	119	-	nC
Q _{gs}	Gate-Source Charge		-	20	-	
Q _{gd}	Gate-Drain Charge		-	26	-	

7. Typical Characteristics




Figure 1. Power Capability




Figure 2. Current Capability




Figure 3. Safe Operation Area




Figure 4. Transient Thermal Impedance




Figure 5. Output Characteristics




Figure 6. $R_{DS(ON)}$ vs. I_D

7. Typical Characteristics (cont.)




Figure 7. Transfer Characteristics




Figure 8. Normalized Threshold Voltage




Figure 9. Normalized On Resistance




Figure 10. Diode Forward Current




Figure 11. Capacitance





Figure 12. Gate Charge

8. Package Dimensions

TO-252 Package



Symbol	Dimensions in Millimeters	
	MIN	MAX
A	2.200	2.400
A1	0	0.127
b	0.660	0.860
c	0.460	0.580
D	6.500	6.700
D1	5.100	5.460
D2	4.830 REF.	
E	6.000	6.200
e	2.186	2.386
L	9.800	10.400
L1	2.900 REF.	
L2	1.400	1.700
L3	1.800 REF.	
L4	0.600	1.000
θ	0°	8°
V	5.600 REF.	