

Super-Junction Power Mosfet

1. Product Information

Features

- Low FOM $R_{DS(ON)} \times Q_G$
- Fast switching capability
- Lead free product is acquired

Applications

- Power supply
- Charger
- Solar/UPS-Micro inverter system


Quick reference

- $V_{DS} \geq 650\text{ V}$
- $I_D \leq 41\text{ A}$
- $R_{DS(ON)} \leq 70\text{ m}\Omega @ V_{GS} = 10\text{ V}$ (Type 80 m Ω)

Pin Description


Pin	Description
1	Gate(G)
2	Drain(D)
3	Source(S)

Simplified Outline



Top View
TO-220

Symbol



Package Marking and Ordering Information

Part number	Marking	Package	Packaging	Quantity	Reel size	Tape width
KJCF65R080C	KJCF65R080C	TO-247	☐ Tape & Reel	N/A	N/A	N/A
			☒ Tube	600 PCS	N/A	N/A

2. Absolute Maximum Ratings ($T_C=25^\circ\text{C}$ unless otherwise noted)

Symbol	Parameter	Values	Unit
V_{DS}	Drain-Source Voltage	650	V
V_{GS}	Gate-Source Voltage	± 30	V
I_D	Continuous Drain Current ($T_C=25^\circ\text{C}$)	41	A
	Continuous Drain Current ($T_C=100^\circ\text{C}$)	26	A
I_{DM}	Pulsed Drain Current	164	A
E_{AS}	Single Pulsed Avalanche Energy (L=18 mH)	840	mJ
P_D	Power Dissipation	357	W
T_J, T_{stg}	Operating Junction and Storage Temperature Range	-55 to 150	$^\circ\text{C}$
$R_{\theta JA}$	Thermal Resistance, Junction-Ambient	42	$^\circ\text{C/W}$
$R_{\theta JC}$	Thermal Resistance, Junction-Case	0.35	$^\circ\text{C/W}$

3. Electrical Characteristics (T_J=25℃, unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Type	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _D =250 μA	650	-	-	V
I _{DSS}	Zero Gate Voltage Drain Current	V _{DS} =650 V, V _{GS} =0 V	-	-	1	μA
		V _{DS} =650 V, T _C =150 °C	-	50	-	μA
I _{GSS}	Gate-Body Leakage Current	V _{GS} =±30 V, V _{DS} =0 V	-	-	±100	nA
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _D =250 μA	3.0	-	4.5	V
R _{DS(ON)}	Drain-Source On-State Resistance	V _{GS} =10 V, I _D =20 A	-	70	80	mΩ
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =100 V, V _{GS} =0 V, f=1 MHz	-	2340	-	pF
C _{oss}	Output Capacitance		-	118	-	pF
C _{rss}	Reverse Transfer Capacitance		-	30	-	pF
Switching Characteristics						
t _{d(on)}	Turn-on Delay Time	V _{DS} =400 V, I _D =20 A, R _G =27 Ω, V _{GS} =10 V	-	83	-	ns
t _r	Turn-on Rise Time		-	82	-	ns
t _{d(off)}	Turn-off Delay Time		-	331	-	ns
t _f	Turn-off Fall Time		-	68	-	ns
R _g	Gate resistance	f=1 MHz	-	6.5	-	Ω
Q _g	Total Gate Charge	V _{DS} =480 V, I _D =20 A, V _{GS} =10 V	-	105	-	nC
Q _{gs}	Gate-Source Charge		-	25	-	nC
Q _{gd}	Gate-Drain Charge		-	40	-	nC
Source-Drain Diode Characteristics						
V _{SD}	Drain-Source Diode Forward Voltage	V _{GS} =0 V, I _F =20 A	-	0.88	1.2	V
Q _{rr}	Reverse Recovery Time	V _R =400 V, I _F =20 A, di/dt=100 A/μs	-	9	-	μC
T _{rr}	Reverse Recovery Charge		-	480	-	ns

4. Electrical Characteristics




Fig 1. Power Capability




Fig 2. Current Capability




Fig 3. Safe Operation Area




Fig 4. Transient Thermal Impedance




Fig 5. Output Characteristics
 $T_J=25^{\circ}\text{C}$




Fig 6. Output Characteristics
 $T_J=150^{\circ}\text{C}$

5. Electrical Characteristics (cont.)




Fig 7. $R_{DS(ON)}$ vs. Gate Voltage




Fig 8. V_{TH} vs. Junction Temperature




Fig 9. Normalized On Resistance




Fig 10. Diode Forward Current




Fig 11. Capacitance





Fig 12. Gate Charge

5. Package Mechanical Data

TO-220 Package



Symbol	Dimensions in Millimeters	
	MIN	MAX
A	4.24	4.70
A1	2.20	3.00
b	0.70	0.95
b1	1.14	1.70
c	0.40	0.60
c1	1.15	1.40
D	28.0	29.8
D1	8.80	9.90
E	9.70	10.50
L1	3.80	
L2	6.25	6.90
L3	2.40	3.00
e	2.54 BSC	