

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- | | |
|---|---|
| ☒ Surface-mounted package | ☒ SGT technology |
| ☒ Fast switching speed | ☒ 100% avalanche tested |
| ☒ $T_{J\max}$ 175°C | ☒ MSL1 |



1.2 Applications

- | | |
|---|--|
| ☒ DC/DC converter | ☒ Power switch |
| ☒ Motor drives | ☒ BMS |

1.3 Quick reference

- | | |
|---|---|
| ☒ $BV \geq 60\text{ V}$ | ☒ $R_{DS(ON)} \leq 0.85\text{ m}\Omega @V_{GS}=10\text{ V}$ |
| ☒ $P_D \leq 357\text{ W}$ | |
| ☒ $I_D \leq 456\text{ A}$ | |

2. Pin Description

Pin	Description	Simplified Outline	Symbol
1~6	Source	 TOLT-16L	
7	Kelvin Source		
8	Gate		
9~16, Tab	Drain		

3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	$T_C=25^{\circ}\text{C}$	60	-	V
V_{GS}	Gate-Source Voltage	$T_C=25^{\circ}\text{C}$	-	± 20	V
I_D	Continuous Drain Current	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}^{[1]}$	-	456	A
		$T_C=100^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	322	A
I_{DM}	Pulsed Drain Current ^[2]	$T_C=25^{\circ}\text{C}, V_{GS}=10\text{ V}$	-	1824	A
P_D	Power Dissipation	$T_C=25^{\circ}\text{C}$	-	357	W
E_{AS}	Single Pulsed Avalanche Energy	$V_{DD}=30\text{ V}, L=0.3\text{ mH}$	-	2160	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	175	$^{\circ}\text{C}$
$R_{\theta JA}$	Thermal Resistance-Junction to Ambient ^[3]		-	50	$^{\circ}\text{C/W}$
$R_{\theta JC}$	Thermal Resistance-Junction to Case		-	0.42	

Notes:

1. Package limited.
2. Pulse width limited by maximum junction temperature.
3. $R_{\theta JA}$ is determined with the device mounted on a 1 in² pad 2 oz copper pad on a 1.5"x1.5" board of FR-4 material.

4. Marking Information

Product Name	Marking
KJ008N06LT1	KJ008N06LT1 XXXXXX-X

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ008N06LT1	TOLT-16L	13"	24 mm	1000

Note: KUAJIEXIN defines "Green" as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C).

6. Electrical Characteristics (T_J=25°C unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV _{DSS}	Drain-Source Breakdown Voltage	V _{GS} =0 V, I _{DS} =250 μA	60	-	-	V
V _{GS(th)}	Gate Threshold Voltage	V _{DS} =V _{GS} , I _{DS} =250 μA	2	3	4	V
I _{DSS}	Drain Leakage Current	V _{DS} =60 V, V _{GS} =0 V	-	-	1	μA
I _{GSS}	Gate Leakage Current	V _{DS} =0 V, V _{GS} =±20 V	-	-	±100	nA
R _{DS(ON)}	On-State Resistance	V _{GS} =10 V, I _{DS} =80 A	-	0.65	0.8	mΩ
R _G	Gate resistance	f=1 MHz	-	1	-	Ω
Diode Characteristics						
V _{SD}	Diode Forward Voltage	V _{GS} =0 V, I _{SD} =50 A	-	0.8	1.1	V
t _{rr}	Reverse Recovery Time	V _{DS} =30 V, I _{DS} =50 A, dI _{SD} /dt=100 A/μs	-	60	-	ns
Q _{rr}	Reverse Recovery Charge		-	75	-	nC
Dynamic Characteristics						
C _{iss}	Input Capacitance	V _{DS} =30 V, V _{GS} =0 V, f=1 MHz	-	14300	-	pF
C _{oss}	Output Capacitance		-	2870	-	
C _{rss}	Reverse Transfer Capacitance		-	270	-	
t _{d(on)}	Turn-on Delay Time	V _{DS} =30 V, V _{GEN} =10 V, R _G =1.6 Ω, I _{DS} =50 A	-	65	-	ns
t _r	Turn-on Rise Time		-	45	-	
t _{d(off)}	Turn-off Delay Time		-	60	-	
t _f	Turn-off Fall Time		-	33	-	
Gate Charge Characteristics						
Q _g	Total Gate Charge	V _{DS} =30 V, V _{GS} =10 V, I _{DS} =50 A	-	200	-	nC
Q _{gs}	Gate-Source Charge		-	66	-	
Q _{gd}	Gate-Drain Charge		-	39	-	

7. Typical Characteristics




Fig 1. Power Capability




Fig 2. Current Capability




Fig 3. Safe Operation Area




Fig 4. Transient Thermal Impedance




Fig 5. Output Characteristics




Figure 6. On Resistance

7. Typical Characteristics (cont.)




Fig 7. Transfer Characteristics




Fig 8. Normalized Threshold Voltage




Fig 9. Normalized On Resistance




Fig 10. Diode Forward Current




Fig 11. Capacitance





Fig 12. Gate Charge

8. Package Dimensions

TOLT-16L Package



Symbol	Dimensions in Millimeters		
	MIN	NOM	MAX
A	2.20	2.30	2.40
A1	0.99	1.04	1.09
A2	0.00	0.08	0.16
A3	1.50 REF		
b	0.70	0.75	0.80
b1	0.65	0.70	0.75
c	0.45	0.50	0.55
D	14.50	15.00	15.50

Symbol	Dimensions in Millimeters		
	MIN	NOM	MAX
D1	9.60	10.10	10.60
D2	2.30	2.80	3.30
D3	5.77 REF		
E	9.40	9.90	10.40
E1	9.46 REF		
E2	8.70 REF		
e	1.15	1.20	1.25
L	2.40	2.45	2.50