KJ0910GM

N-Channel Enhancement Mode MOSFET

1. Product Information

1.1 Features

- ☑ Surface-mounted package
- ☑ Low Thermal Resistance

1.2 Applications

- ☑ Motor driver appliances
- ☑ High power inverter system
- ☑ Adapter appliances

1.3 Quick reference

- ☑ BV ≧ 100 V
- ☑ $R_{DS(ON)}$ ≦ 9.5 mΩ @V_{GS} = 10 V
- ☑ P_D ≦ 67 W
- ☑ $R_{DS(ON)}$ ≦ 13.5 mΩ @V_{GS} = 4.5 V
- ☑ I_D ≦ 64 A

2. Pin Description

Pin	Description
1,2,3	Source
4	Gate
5,6,7,8	Drain

Simplified Outline



Top View
PDFN5x6-8L

Symbol



3. Limiting Values

Symbol	Parameter	Conditions	Min	Max	Unit
V_{DS}	Drain-Source Voltage	T_C=25℃	-	100	V
V_{GS}	Gate-Source Voltage	T_C=25℃	-	±20	V
I_D *, ***	Drain Current (DC)	T_C=25℃, V_{GS}=10 V	-	64	A
		T_C=100℃, V_{GS}=10 V	-	40	A
I_{DM} *	Pulsed Source Current	T_C=25℃, V_{GS}=10 V	-	256	A
P_D	Power Dissipation	T_C=25℃	-	67	W
E_{AS} *	Single Pulsed Avalanche Energy	V_{DD}=50 V, L=0.5 mH	-	392	mJ
T_J, T_{stg}	Operating Junction and Storage Temperature Range		-55	150	℃
$R_{\theta JA}$**	Thermal Resistance-Junction to Ambient		-	56	℃/W
$R_{\theta JC}$	Thermal Resistance-Junction to Case		-	1.85	

Notes:

* Pulse width ≤ 300 μs, duty cycle ≤ 2%.

** Surface mounted on 1 in^2 pad area, t ≤ 10 sec.

*** Limited by bonding wire.

4. Marking Information

Product Name	Marking
KJ0910GM	**KJ0910GM XXXXXX**

5. Ordering Code

Product Name	Package	Reel size	Tape width	Quantity (pcs)
KJ0910GM	**PDFN 5x6-8L**	**13"**	**12 mm**	**5000**

Note: KUAIJIEXIN defines “Green” as lead-free (RoHS compliant) and halogen free (Br or Cl does not exceed 900 ppm by weight in homogeneous material and total of Br and Cl does not exceed 1500 ppm by weight; Follow IEC 61249-2-21 and IPC/JEDEC J-STD-020C).

6. Electrical Characteristics (T_A=25℃ unless otherwise noted)

Symbol	Parameter	Conditions	Min	Typ	Max	Unit
Static Characteristics						
BV_{DSS}	Drain-Source Breakdown Voltage	V_{GS}=0 V, I_{DS}=250 μA	100	-	-	V
$V_{GS(th)}$	Gate Threshold Voltage	V_{DS}=V_{GS}, I_{DS}=250 μA	1.2	1.8	2.6	V
I_{DSS}	Zero Gate Voltage Source Current	V_{DS}=80 V, V_{GS}=0 V	-	-	1	μA
I_{GSS}	Gate Leakage Current	V_{DS}=0 V, V_{GS}=±20 V	-	-	±100	nA
$R_{DS(ON)}$ [a]	On-State Resistance	V_{GS}=10 V, I_{DS}=230 A	-	8.5	9.5	mΩ
		V_{GS}=4.5 V, I_{DS}=10 A	-	10.5	13.5	
g_{FS} [b]	Forward Transconductance	V_{GS}=5 V, I_{DS}=10 A	-	30	-	S
R_g	Gate Resistance	f=1 MHz	-	0.6	-	Ω
Diode Characteristics						
V_{SD} [a]	Diode Forward Voltage	I_{SD}=20 A, V_{GS}=0 V	-	0.9	1.3	V
t_{rr}	Reverse Recovery Time	I_{DS}=20 A, V_{GS}=0V dI_{SD}/dt=100 A/μs	-	43	-	ns
Q_{rr}	Reverse Recovery Charge		-	36	-	nC
Dynamic Characteristics [b]						
C_{iss}	Input Capacitance	V_{GS}=0 V, V_{DS}=50 V Frequency=1 MHz	-	1644	-	pF
C_{oss}	Output Capacitance		-	359	-	
C_{rss}	Reverse Transfer Capacitance		-	13.5	-	
$t_{d(on)}$	Turn-on Delay Time	V_{DS}=50 V, V_{GEN}=10 V, R_G=3 Ω, I_{DS}=20 A	-	17	-	ns
t_r	Turn-on Rise Time		-	1	-	
$t_{d(off)}$	Turn-off Delay Time		-	43	-	
t_f	Turn-off Fall Time		-	8.2	-	
Gate Charge Characteristics [b]						
Q_g	Total Gate Charge	V_{DS}=50 V, V_{GS}=10 V, I_{DS}=30 A	-	29	-	nC
Q_{gs}	Gate-Source Charge		-	5.6	-	
Q_{gd}	Gate-Drain Charge		-	6.5	-	

Notes:

a. Pulse test; pulse width ≤ 300 μs, duty cycle ≤ 2%.

b. Guaranteed by design, not subject to production testing.

7. Typical Characteristics



Figure 1. Output Characteristics



Figure 2. Transfer Characteristics



Figure 3. Drain-to-Source On Resistance vs Drain Current



Figure 4. Body Diode Forward Voltage vs Source Current and Temperature



Figure 5. Capacitance Characteristics



Figure 6. Gate Charge Characteristics

7. Typical Characteristics (cont.)



Figure 7. Normalized Breakdown Voltage vs Junction Temperature



Figure 8. Normalized On Resistance vs Junction Temperature



Figure 9. Maximum Continuous Drain Current vs Case Temperature



Figure 10. Maximum Power Dissipation vs Case Temperature



Figure 11. Drain-to-Source On Resistance vs Gate Voltage and Drain Current



Figure 12. Maximum Safe Operating Area

7. Typical Characteristics (cont.)



Figure 13. Maximum Effective Transient Thermal Impedance, Junction-to-Case

8. Package Dimensions

PDFN 5x6-8L Package



Symbol	Dimensions in Millimeters	
	Min	Max
A	1.03	1.17
A1	0.82	0.97
b	0.34	0.48
D	4.80	5.40
D1	4.80	5.00
D2	4.11	4.31
E	5.95	6.15
E1	5.65	5.85
E2	1.60	-
e	1.270 BSC	
L	0.05	0.25
L1	0.38	0.50
L2	0.38	0.50
H	3.30	3.50
t	-	0.18